

T: (905) 625-1758 | F: (905) 625-0187







SERVICE





ENERGY SAVING SOLUTIONS



PREVENTIVE MAINTENANCE PROGRAM



EQUIPMENT INSTALLATION



Work Order No.: WO82696

Customer Name: Allan's Your Independant Grocery Location: 1900 Dixie Road, Pickering, ON

Inspection Date: August 16th, 2021 **NDS Tech:** Nick Leusenko

Position	Summary
Position 1 – Door	Requires: - Bottom section at 8' 2" x 24" white - Top weather seal
	Make and Model: TX450
	Door Size: 8' 2" x 10'
Position 2 – Door	Requires: - Bottom section at 8' 2" x 24" white - Intermediate section at 8' 2" x 21" white
	Make and Model: TX450 Door Size: 8' 2" x 10'
Position 1 – Dock	In good working condition
Position 2 – Dock	In good working condition





T: (905) 625-1758 | F: (905) 625-0187


Description Cleaned

Pictures



Position 1 – Door

Damaged bottom section and top weather seal



Damaged bottom and intermediate section







www.northerndocksystems.com T: (905) 625-1758 | F: (905) 625-0187

					エ~	1051	ns.	10A	7	-18			_		
Northern	Customer Na	umo A	4	الم	5 6	SAG	x3n	405	Tech		- 55	~	=0	12	-
Dock Systems	Sits Location	19	000	25	KIS	K	0	Insp	ection	Date	0	1	+	12	_
	BEFORE ENTER		~		-			WO	AUNITE			6 9	6	TOF	V PLAC
1.866.601.1758 www.northerndocksystems.com	Position # 1	CING L	JOCKI	PITE	OTHI		PRU	VEUN	DECEMBER 1	190190	-	VIAPAG	-		MAN
PREVENTATIVE MAINTENANCE	Manufacturar >	-	1_	~/	2000	2		-	-			-	-	Н	
PMP PROGRAM		Model > SHLF 6 8 sanicel or Ar > H						-	-		Н				
	chanical or Air >				H										
	ork area secure >														
Look out / Tag out pro	cedure followed >		/		-	/					_		_	-	-
DOCK LEVELER INSPECTION	N SHEET	200	. 10	3	100	. 8	10	1232	. 4	9		V 70	8		, 19
		000	NO ACE	080V	1000	NORW CH	1080	8	0 A	8	8	0 6	080	000	9 N
Check full operating cycle	ok maala	1			1	-									
Inspect condition of rear ourb angle and welds to do Inspect side weather seal	ck angle	1	-						-			-			
Inspect deck for any dishing or signs of structural we	ear			Н	1		Н			Н			н		
Inspect rear deck hinge				П	1		П			П					
Clean, Lubricate and Inspect front lip hinge		1													
Inspect factory maintenance strut		1		Ц	1		Ц								
Clean pit of debris Inspect all structural components and shims for brol	one confete	1		H	K	+	H	H	3 10			+	Н		
Inspect dock lip and drown	ren weids			Н		-	Н	Н		Н	Н		Н		+
Inspect shims				Н			П	Н		Н		+			
Inspect dock bumper condition	THE TIME	1			1										
inspect dock seal and/or shelter						200	Ш								
Inspect toe guards	A 100 100 100	1		Н	1		H								
Lubricate rear hinges and all pivot points HYDRAULIC	THE RESERVE	100	4 4			1 2				100	-	_	ш		
Run power unit - listen for abnormal noise		1		П	1		П						ī		
Inspect oil level and top up as needed	2 60 E				1										
Ensure power unit tank cap is secured		1		Ш	4										
Inspect all electrical components	-1			Н		-	H								
Inspect lip and main cylinders bracket and mounting Inspect cylinder shaft seals for oil leaks	pins	1		Н	1		Н	Н	-						
Inspect hydraulic hoses and fittings for oil leaks		1		Н	1		Н	Н	-	Н		-	-		
MECHANICAL	H HELLE	0	-	100	ALC:	5 3	(8)	000	SC N	100	0	8 3	100	765	5 3
Inspect pull chain												T	T		
Inspect lifting springs and adjust tension as required															
Inspect, lubricate and adjust hold down as required AIR	Charles and the Control of the Contr	100000	_	Ц			Ц								
Run power unit - listen for abnormal noise			No.		800	200	-	0	F. 10.00	1	0	2 7	-	-	2 1
Inspect air bag for punctures or tears			+	Н	\vdash		Н	Н	-						
Visually Inspect all electrical components				Н		100	Н	Н							
Inspect and lubricate pull action chain															
Inspect lip kick out mechanism															
Loading dock and interlocks cycle tested for proper operation				If ar	ny sa	fety c	once	rns i	otify	cust	ome	r imn	nedia	tely	





www.northerndocksystems.com T: (905) 625-1758 | F: (905) 625-0187

	Customer Name	LLA	25	91	PEI	EN				_	-	5	IL	-	-
Northern	Site Location (9	000	0	EXI	E	RO		insp	ection	Section 1	1	3/	17	12	-1
Dock Systems								WO	No.	- 10		64	6		
1,886,801,1758 www.northerndocksystems.com	ALL ADJUSTMENTS	S ABOV	/E 10	AS P	ER ON	TARIO	REG	ULAT	ON 21	3/91 V	VILL R	EQUIR	EAS	CISSC)R
	Position #	_	1			2									H
PREVENTATIVE MAINTENANCE	Make and model	TX	4.	50	TX	45	0			-			-1	-	
PMP PROGRAM	Door size	81	LK	10	812	UL	0	H					-1		
	Door lift type 3		- 12	-											
	Work area secure		1	-		-							-	_	
	Tag out procedure followed	-	-	- 4		_	2	0	× 2	2	9 1	2	7	8 #	
SECTIONAL OVERHEAD DOPERATOR INSPECTION		noon	NOSS.	STATE	1000	SPLACE .	Bruces	000	DION DELACE	aona	8 1	PUGE .	yuoso	00 MM	-
Inspect and secure lower jambs and door track, straighte	en if required	1			1			Н					Н		ł
Inspect sections			1			-		H						1	f
Inspect and lubricate rollers Inspect and lubricate hinges		1			1			H							I
Inspect bottom bracket														1	I
Inspect and adjust slide lock	A STATE OF THE REAL PROPERTY.	1			1			H	1						H
Inspect and secure lift handle and step plate Inspect pull rope	N O'S ASSESSMENT OF THE PARTY O	1			M			H						3	Ħ
Inspect cables		1			1										I
Inspect side weather seal	SERVICE STREET	1			1			П							H
Inspect top weather seal	The second secon		-	1	1			H							H
Inspect bottom weather seal (rubber and or brush) Inspect and clean windows			1000		K			Ħ	-	1000					t
Inspect and secure track guards	SINGLE DIS	1			1	2 0			9 5						
Inspect chain hoist		1			1			Н						+	L
Inspect and secure upper jambs and track, straighten if Inspect and lubricate head shaft bearings	required		1000				100	F	100			900		100	P
Inspect shaft	All the second	1		6 50	1	9 59			0 60	100		93		8	t
Inspect and secure drum		M			M									T	Ι
Inspect and secure coupler Inspect, secure and lubricate main spring		1	100	10000		100	100	100						9	P
Adjust tension on main spring	SALES AND DESCRIPTION OF THE PERSON OF THE P	1	00	0 80	1	10			0 00			100		100	t
Inspect and secure back hanging (if present)	-														Ī
Inspect and secure bumper, leaf or pusher springs ELECTRIC OPERATOR AND SAFETIES	CONTRACTOR OF THE PARTY OF THE	1			1	-									1
Inspect and lubricate drive chains and sprockets	NAME AND ADDRESS OF TAXABLE PARTY.								3 1		7			2 3	
inspect bearings and shafts									100	100		8 88	Н		t
Inspect and test clutch assembly															Ī
Adjust open and close limit switches if required Inspect and adjust drive belt		-		3 (0)	-									0 9	I
Inspect and tighten mounting bolts / plates			223	300		100		100	99 60		Н			-	+
Inspect and test emergency chain hoist and manual disc	connect									П			H		Ŧ
Inspect and test photo eyes Inspect and test opening devices (loops, pull cords, etc.)				40		0	-					1			İ
Inspect and test push buttons	Printer America		100	900		100		100							1
Inspect and test reversing safety edge				8			T			H		1		-	1
Door, opening devices and all safeties cycle tested for p	POPPE AD ALLE				any sa	afety o			notify	cust	omer	imm	ediate	ily	1
NOTES: DESCRIPTION ADVISE PARTICULARS IN DI #I BOTTOM SECTION (#2 BOTTOM SECTION @ 8 SECTION @ 82"x21" TA	28'2×24"	T7 45	× 5	15	0	WH E,	T	- TE / -	TO	P	W	15 CA			